

# Panel PC

## ARTEMIS M/F

### 15" Multimedia Panel PC



## Specifications

- CPU
  - ◆ ARTEMIS M: Intel Celeron M 1.5 GHz up to Pentium M 2.0 GHz
  - ◆ ARTEMIS F: Intel on board Celeron M 1.0 GHz
- System Chipset
  - ◆ Artemis M/F: Intel 852 GM/ICH4
- System Memory:
  - ◆ 2 x 184 pin DDR to 2GB
- System Display
  - ◆ 15" TFT LCD, 1024 x 768
  - ◆ Share memory architecture able to utilize the display memory up to 64MB
- Standard I/O
  - ◆ Serial ports x 4 (COM 1, 2 & 4 with +5V/12V power output on pin 9; COM 2 is selectable for RS-232/422/485; COM3 is internal type reserved for touchscreen)
  - ◆ Parallel port x 1 (SPP/EPP/ECP)
  - ◆ PS/2 keyboard interface x 1
  - ◆ PS/2 mouse interface x 1
  - ◆ DIO: Input x 2, output x 2
  - ◆ USB interface x 4
  - ◆ VGA interface x 1 (DB15 connector, support extension display function)
  - ◆ +5V/+12V DC-out: x 1
- Expansion Slot
  - ◆ Mini PCI x 1
- Audio
  - ◆ Speaker x 2
  - ◆ MIC-in/speaker-out
- Ethernet
  - ◆ 10/100 Base-T Ethernet with RJ-45
  - ◆ Supports Wake-on-LAN
- Front Bezel
  - ◆ LED indicators for HDD, LAN, POWER
- Power Supply
  - ◆ 120W, 100~240V, 1.2A @50~60Hz

## Peripheral & Storage Devices

- Touchscreen:
  - ◆ 15" Resistive type or SAW type
- Drive Bay
  - ◆ 2.5" HDD x 1 (option)
  - ◆ Slim CD-ROM or equivalent device x 1 (option)
  - ◆ Compact Flash x 1 (option)

## Mechanical / Environmental

- Construction
  - ◆ Inside: Heavy-duty steel
  - ◆ Outside: Fire-proof resilient plastic
- Mounting
  - ◆ Wall mount & VESA mount
- Versatile Stand
  - ◆ 3-stage standing



3 stage ▲  
versatile stand



Wall mount with ▲  
scanner and MSR



Wall mount with ▲  
media card reader