

RACK-Console RLM-150

15" Foldable 1U Height
Rack-mounting LCD Monitor

LKM-926A

15" LCD Monitor/Keyboard/Mouse/
Speaker 4-in-1 1U Height Drawer

LCD




LKM-926A
Two self-clinchings prevents the
keyboard sliding in shaking

RLM-150 is intelligently designed with its foldable 1U height rack-mounting feature, which minimizes space utilization of server racks. The two self-clinching locks stabilize the monitor position and prevent it from sliding out in all circumstances.

The equipped analog VGA input function of RLM-150 enables an easy use of LCD panel without the need to concern about the VGA card type. Its high level of compatibility ensures a stable and quality performance with almost all sorts of computers, workstation and servers.

2 self-clinching locks to stabilize
the monitor position



SPECIFICATIONS

- ◆ 1U Height designed to save rack space
- ◆ Plastic front panel
- ◆ Material : Heavy-duty steel
- ◆ The front panel of RLM-150 has two self-clinchings with lock
- ◆ 15" high brightness TFT LCD
Resolution : 1024x768 XGA
Brightness : 250cd/m²
LCD MTBF : 50,000 hrs
Backlight MTBF : 30,000 hrs
Panel color : 262K display color
Viewing angle : 160°(Horizontal) x 160°(Vertical)
Pixel Pitch : 0.297(H) x 0.297(W)
Contrast ratio: 400 : 1 typical
- ◆ Front OSD control keys to adjust the best display quality
- ◆ Standard D-sub 15 Pin VGA Input connector
- ◆ Ship with power adapter for 100~240 VAC input
- ◆ Optional resistive type touch screen with RS-232 interface
- ◆ Color : White(PANTONE 413C) , Black (PANTONE Black)
- ◆ Storage temperature : -20~60°C
- ◆ Operating temperature : 0~50°C
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640 Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Relative Humidity : 5~95% , non-condensing
- ◆ Depth : 520 mm
- ◆ Net/GW : 9/17(kg)

SPECIFICATIONS

- ◆ Only 1U designed to save RACK space
- ◆ The front panel of LKM-926A has two self-clinchings with lock
- ◆ 15" high brightness TFT LCD display
Resolution: 1024 x 768
LCD Color: 262K
Pixel Pitch: 0.297x0.297mm
Brightness: 200 cd/m²
Contrast ratio: 400:1 (Typ.)
LCD MTBF: 50,000 hrs
Backlight: 25,000hrs
- ◆ LKM-926A with 88key slim size keyboard ,
- Supports English, Japanese, German, French and Italian Language
- ◆ Touchpad with two key buttons
- Microsoft Mouse compatible with PS/2 mouse interface
- ◆ Accepts audio input and built-in two speakers
- ◆ Built-in OSD for user adjustment , including H/V position , color ,size, etc
- ◆ Power Supply:
Built-in universal AC input adapter
ACE-802T, 36VDC~72VDC input, 12V@2A output
ACE-802C, 20VDC~30VDC input, 12V@2A output
- ◆ Depth: 525mm
- ◆ Operating temperature: 0~ 50°C
- ◆ Net/GW (kg): 11.2/16.8

LKM-CBXXA



ORDERING INFORMATION

- **LKM-926A** [C] - [L]:
Single Input 15" LCD/Keyboard/Mouse/Speaker 1U drawer
includes 1.1M length cable set.AC Input
 - **LKM-926A** [CT] - [L]:
Single Input 15" LCD/Keyboard/Mouse/Speaker 1U drawer
includes 1.1M length cable set. 48VDC input
 - **LKM-926A** [C] -24V -[L]:
Single Input 15" LCD/Keyboard/Mouse/Speaker 1U drawer
includes 1.1M length cable set. 24VDC input
- [C] Color Code B: Black W: White
[L] Language Code
EN:English, JP:Japanese,DE:German, FR:French, IT:Italian

ORDERING INFORMATION

- **RLM-150** [C] 1U Height 15" Foldable LCD Monitor
[C]: Color code W: WHITE B: BLACK
Option : T-R151B 15" 3M resistive touch screen

- Option:**
- **LKM-CB18A** 1.8M cable set, includes VGA, Keyboard, Mouse & Audio cable
 - **LKM-CB30A** 3.0M cable set, includes VGA, Keyboard, Mouse & Audio cable
 - **LKM-CB50A** 5.0M cable set, includes VGA, Keyboard, Mouse & Audio cable