



Sunlight Readable LCD!

Advanced  
Brightness  
Technology™

**Key Features:**

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Short Response Time
- Thin and Light



## LD1226(Toshiba LTD121EA43G)

|                               |  |
|-------------------------------|--|
| <b>Model No.</b>              | LD1226   |
| <b>LCD Display</b>            | 12.1" TFT Active Matrix Panel  |
| <b>Brightness</b>             | 1250 cd/m <sup>2</sup>   |
| <b>Pixel Pitch(mm)</b>        | 0.24(H)x0.24(V)  |
| <b>Max. Resolution</b>        | 1024x768 (XGA)   |
| <b>Contrast Ratio</b>         | 500:1  |
| <b>Display Area</b>           | 245.76x184.32mm  |
| <b>Response Time(Typ.)</b>    | 50ms (Max)   |
| <b>Display Colors</b>         | 262,144 colors   |
| <b>Viewing Angle</b>          | +70°~-70°(H), +55°~-70°(V)   |
| <b>Video</b>                  | RGB Analog 0.7V Peak to Peak   |
| <b>Sync</b>                   | LVDS   |
| <b>Signal Connector</b>       | 15 Pin D-sub   |
| <b>F/ R Control Button</b>    | Power Switch, Menu, Select (+, -), Auto                                |
| <b>OSD Menu</b>               | Brightness, Contrast, H/V Position,<br>Color, Phase, Clock, Management |
| <b>S-video / AV connector</b> | Optional   |
| <b>Power Consumption</b>      | 32W  |
| <b>Dimensions (mm)</b>        | 338x278x59.3mm   |
| <b>Weight (Net)</b>           | 3.07kg   |
| <b>Inverter</b>               | LI2002   |
| <b>Control Board</b>          | RTD2020  |

> LD Display ----- LH+Display Housing

*Specifications are subject to change without notice.*

*All brands or product names are trademarks or registered trademarks of their respective companies.*