



Sunlight Readable LCD!

Advanced
Brightness
Technology™

Key Features:

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Short Response Time
- Thin and Light



LD1544 / 48 (AU150XN07)

Model No.	LD1544 / LD1548
LCD Display	15" TFT Active Matrix Panel
Brightness	800 cd/m ² / 1600 cd/m ²
Pixel Pitch(mm)	0.297(H) x 0.297(V)
Max. Resolution	1024x 768
Contrast Ratio	400 :1
Display Area	304.128x 228.096mm
Response Time(Typ.)	16ms(Typ.)
Display Colors	262,144 Colors
Viewing Angle	+60 °~-60 °(H), +40 °~-60 °(V)
Video	RGB Analog 0.7V Peak to Peak
Sync	LVDS
Signal Connector	15 Pin D-sub, 29 Pin DVI-D
F/ R Control Button	Power Switch, Menu, Select (+, -), Auto
OSD Menu	Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
PAL / NTSC / S-video / AV connector	Standard
Power Consumption	56.5W
Dimensions (mm)	389x325x60.5
Weight (Net)	3.92kg
Inverter	LI2203
Control Board	LM1513
Option	Touch (Resistive/ Capacitive) Light Sensor, VR Control
Certification	CE, FCC

> LD Display----- LH+Display Housing

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.