



Sunlight Readable LCD!


Advanced
Brightness
Technology™

Key Features:

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Short Response Time
- Thin and Light



Inverter
LI2701



Control Board
RTD2020



LF/LH1041 (AU-10.4B104SN05)

Model No.	LF1041	LH1041
LCD Display	10.4" TFT Active Matrix Panel	10.4" TFT Active Matrix Panel
Brightness	1500 cd/m ² (6 CCFL)	1500 cd/m ² (6 CCFL)
Pixel Pitch(mm)	0.264(H) x 0.264(V)	0.264(H) x 0.264(V)
Max. Resolution	800x 600 SVGA	800x 600 SVGA
Contrast Ratio	500:1	500:1
Display Area	211.2 x 158.4mm	211.2 x 158.4mm
Response Time(Typ.)	35ms(Typ.)	35ms(Typ.)
Display Colors	262,144 colors	262,144 colors
Viewing Angle	+60°~-60°(H), +40°~-60°(V)	+60°~-60°(H), +40°~-60°(V)
Video		RGB Analog 0.7V Peak to Peak
Sync		LVDS
Signal Connector		15 Pin D-sub
F/ R Control Button		Power Switch, Menu, Select (+, -), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
S-video / AV connector		optional
Power Consumption	25W	30W
Dimensions (mm)	283x184x27.2mm	283x184x27.2mm
Weight (Net)	0.68kg	0.75kg
Inverter	LI2701	LI2701
Control Board		RTD2020

> LF Openframe ----- VHB/UB/HB(Panel+Inverter)

> LH Openframe ----- VHB/UB/HB(Panel+Inverter+Control Board+OSD Board+VGA Connector Board)

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.