



Sunlight Readable LCD!



Key Features:

- Very High Brightness
- Wide Viewing Angle
- High Contrast Ratio
- LVDS
- Long Lamp Life
- Short Response Time
- Thin and Light



LF/LH1544 / 48 (AU150XN07)

Model No.	LF1544 / LF1548	LH1544 / LH1548
LCD Display	15" TFT Active Matrix Panel	15" TFT Active Matrix Panel
Brightness	800 cd/m ² / 1600 cd/m ²	800 cd/m ² / 1600 cd/m ²
Pixel Pitch(mm)	0.297(H) x 0.297(V)	0.297(H) x 0.297(V)
Max. Resolution	1024x 768	1024x 768
Contrast Ratio	400 :1	400 :1
Display Area	304.128x 228.096mm	304.128x 228.096mm
Response Time(Typ.)	16ms(Typ.)	16ms(Typ.)
Display Colors	262,144 colors	262,144 colors
Viewing Angle	+70°~-70°(H), +50°~-70°(V)	+70°~-70°(H), +50°~-70°(V)
Video		RGB Analog 0.7V Peak to Peak
Sync	LVDS	LVDS
Signal Connector		15 Pin D-sub, 29 Pin DVI-D
F/ R Control Button		Power Switch, Menu, Select (+, -), Auto
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
S-video / AV connector		Standard
Power Consumption	51.5W	56.5W
Dimensions (mm)	326.5x253.5x19.46	326.5x253.5x19.46
Weight (Net)	1.7kg	1.75kg
Inverter	LI2203	LI2203
Control Board		LM1513

> LF Openframe ----- VHB/UB/HB(Panel+Inverter)

> LH Openframe ----- VHB/UB/HB(Panel+Inverter+Control Board+OSD Board+VGA Connector Board)

Specifications are subject to change without notice.

All brands or product names are trademarks or registered trademarks of their respective companies.