





Sunlight Readable LCD!



- MVA technology, no viewing limit
- High contrast: 800:1
- High resolution: 1280x1024 SXGA
- High brightness: 700 nits
- Narrow boarder design



LI3801 Inverter



Control Board
AD2523



LF/LH1946(AU M190EN03)

Model No.	LF1946	LH1946
LCD Display	19" TFT Active Matrix Panel	19" TFT Active Matrix Panel
Brightness	700 cd/m ²	700 cd/m ²
Pixel Pitch(mm)	0.294(H) x 0.294(V)	0.294(H) x 0.294(V)
Max. Resolution	1280x 1024	1280x 1024
Contrast Ratio	800:1	800:1
Display Area	376.32 x 301.056mm	376.32 x 301.056mm
Response Time(Typ.)	20ms(Typ.)	20ms(Typ.)
Display Colors	16.7M colors	16.7M colors
Viewing Angle	+85°~-85°(H), +85°~-85°(V)	+85°~-85°(H), +85°~-85°(V)
Video		RGB Analog 0.7V Peak to Peak
Sync	LVDS	LVDS
Signal Connector		15 Pin D-sub, 29 Pin DVI
F/ R Control Button		Power Switch, Menu, Select (+, -), Source Key
OSD Menu		Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
S-video / AV connector		Standard
Power Consumption	63W	68W
Dimensions (mm)	404.6x330x23.5mm	404.6x330x23.5mm
Weight (Net)	2.1kg	2.5kg
Inverter	LI3801	LI3801
Control Board		AD2523

Specifications are subject to change without notice.
All brands or product names are trademarks or registered trademarks of their respective companies.

Digital Technology, Inc.
Covington, LA 70435
USA
Tel: 985 809 1766
FAX: 985 809 1665
www.digitaltechinc.com

Copyright 2005
LM20050510